

CLEANOUT™

Tank Cleaning **Power**

■ PRINCIPAL FUNCTIONING AGENTS

Organic amine, inorganic hydroxides, surfactants, and formulation aids . . . 100.00%

All ingredients are exempt from the requirement of a tolerance as specified in 40 CFR Part 180.1001 (c) and (d).



Shake Well Before Using
LVD0126

GUARANTEED AND DISTRIBUTED BY

POWERAG™

powerag.com

NET CONTENTS
1 QT



CLEANOUT™
powerag.com

Guaranteed and Distributed by

POWERAG™

Shake Well Before Using

GENERAL INFORMATION: CleanOut aids in the reduction of spray tank residue. Since the amount of residue varies, individual conditions will directly affect use rates of CleanOut.

USE RATES: 1 quart of CleanOut treats up to 100 gallons of spray solution. Circulate cleaning solution throughout entire system. Use high pressure spray to clean and rinse interior of spray tank. Purge tank systems, spray lines and nozzles. Drain out and completely rinse tank again using clean water. **Always use enough CleanOut to completely remove all residues.**



CONTAINS POTASSIUM HYDROXIDE AND SODIUM METASILICATE

DANGER: Causes severe burns and eye damage. Do not breathe dusts or mists. Wash all exposed skin thoroughly after handling. Wear protective gloves, protective clothing, eye protection, and face protection. **If swallowed:** Rinse mouth. Do NOT induce vomiting. **If on skin (or hair):** Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. **If inhaled:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse. Store locked up. See safety data sheet for further details regarding the safe use of this product.

STORAGE AND DISPOSAL: Do not contaminate water, food, or feed by storage or disposal. Protect from freezing. Store above 32°F. Do not store near strong oxidizing materials, acids, or chlorine. Do not reuse empty container. Dispose of in a safe manner in accordance with local, state, and federal regulations.

CONDITIONS OF SALE: Seller warrants that the product contains the ingredients in the amounts stated on this label. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES AND REPRESENTATIONS EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE. Timing, rate and method of application, weather and other conditions, mixtures with chemicals not specifically recommended on this label or any accompanying written recommendation are beyond the control of Seller. Buyer assumes all risks of use, storage, and handling of this material not in strict accordance with directions given herewith. In no case is Seller liable for consequential, special, or indirect damages resulting from the use or handling of this product. Buyer further agrees in the event of damages arising from the use of this product to accept a replacement of the product or a refund of the purchase price of the product, at Seller's option, as full discharge of Seller's liability. No one is authorized to make any other warranty, guarantee, or directions concerning this product, and no such warranties, guarantees, or directions shall be valid or binding upon Seller.

LVD0126

FREEZING TEMPERATURE: 32°F (protect from freezing) **WEIGHT PER QUART:** 2.3 Pounds

GUARANTEED AND DISTRIBUTED BY **PowerAG:** 2213 LEABROOK ROAD, LANCASTER, PA 17601 • 800.842.2578